

機械規格 MACHINE SPECIFICATION

★ 因長期研發，機械設計如有變更恕不另行通知。
★ We reserve the right to change the above design without prior notification.

項目 ITEMS			金鑽12 DIAMOND 12	金鑽12CS DIAMOND 12CS	金鑽16 DIAMOND 16	金鑽16CS DIAMOND 16CS
加工範圍 Working Rang	最大加工外徑	Max. Machining dia.	ø12.7mm	ø12.7mm	ø16.5mm	ø16.5mm
	最大加工長度	Max. machining length per chucking	145mm	145mm	145mm	145mm
	最大鑽孔直徑	Max. drilling dia.	ø7mm	ø7mm	ø10mm	ø10mm
	最大攻牙外徑	Max. tapping dia.	M6	M6	M8	M8
外徑刀 O.D Tooling	刀具數	Number of tools	6	6	6	6
	刀具尺寸	Dimension	□10X10X100	□10X10X100	□10X10X100	□10X10X100
內徑刀 I.D. Tooling	刀具數	Number of tools	4	4	4	4
	刀具尺寸	Dimension	7mm (ER11)	7mm (ER11)	10mm (ER16)	10mm (ER16)
側面鑽銑刀 Cross Working Driven Tooling	刀具數	Number of tools	-	4	-	4
	刀具尺寸	Dimension	-	7mm (ER11)	-	10mm (ER16)
	刀具轉速	Speed	-	200~3000rpm	-	200~3000rpm
正面鑽銑刀 Front Working Driven Tooling	刀具數	Number of tools	-	3	-	3
	刀具尺寸	Dimension	-	7mm (ER11)	-	10mm (ER16)
	刀具轉速	Speed	-	200~3000rpm	-	200~3000rpm
主軸 Main Spindle	主軸內徑	Spindle hole dia.	ø13mm	ø13mm	ø17mm	ø17mm
	主軸轉速	Spindle speed	200~8,000rpm	200~8,000rpm	200~8,000rpm	200~8,000rpm
快速位移 Rapid Traverse	主軸定位角度	Spindle indexing angle	-	C axis (opt. CS axis 0.01° indexing)	-	C axis (opt. CS axis 0.01° indexing)
	X1, Y1, Z1軸	X1, Y1, Z1 axes	30M	30M	30M	30M
馬達 Motors	主軸馬達	Main spindle motor	2.2kW	2.2kW	2.2kW	2.2kW
	X/Y/Z 軸馬達	X1, Y1, Z1 axes motor	1kW	1kW	1kW	1kW
	切削馬達	Coolant pump	1/4 HP	1/4 HP	1/4 HP	1/4 HP
	潤滑油馬達	Lubrication	4w	4w	4w	4w
	側銑馬達	Driven tools motor	-	1kW	-	1kW
機械尺寸 Machine Dimensions	主軸中心高	Center height	1050mm	1050mm	1050mm	1050mm
	重量	Weight	1188kg	1208kg	1220kg	1240kg
	機械尺寸	Machine dimension	1200x900x1750mm			
氣壓 Air Pressure	空氣壓力	Air pressure	5kg/cm	5kg/cm	5kg/cm	5kg/cm
	空氣量	Air supply	10L/min	10L/min	10L/min	10L/min
選配 OPTIONAL						
簡易背軸 (尾夾) Simple Sub-spindle (Rear Clamping Device)	簡易背軸馬達	Simple sub-spindle motor	1kW	1kW	1kW	1kW
	簡易背軸轉速	Simple sub-spindle speed	3000rpm	3000rpm	3000rpm	3000rpm
	Z2 軸馬達	Z2 axis motor	1kW	1kW	1kW	1kW
	Z2 軸快速位移	Z2 axis rapid traverse	18M	18M	18M	18M
	背面內徑刀具數	Number of back I.D Tools	4	4	4	4
	背面內徑刀具尺寸	Dimension of back I.D Tools	7mm (ER11)	7mm (ER11)	10mm (ER16)	10mm (ER16)
	機械重量	Machine weight	1350kg	1370kg	1390kg	1410kg
機械尺寸	Dimension	1882x1246x1860mm				

機械配件 MACHINE ACCESSORIES :

● 標準配備 Standard ● 選擇配備 Option — 無 N/A

項目 ITEMS		金鑽12 DIAMOND 12	金鑽12CS DIAMOND 12CS	金鑽16 DIAMOND 16	金鑽16CS DIAMOND 16CS
主軸C軸定位	Main spindle C axis indexing	—	●	—	●
工件切斷檢測	Part off detective sensor	●	●	●	●
冷卻系統	Coolant system	●	●	●	●
工作燈	Working light	●	●	●	●
收料器	Part catcher	●	●	●	●
鐵屑盒	Chip tray	●	●	●	●
固定式套筒	Fixed bushing	●	●	●	●
側銑刀具刀座	Cross working driven tool holder	—	●	—	●
正面偏心鑽銑刀具刀座 (選配簡易背軸無此配置)	Front off-center driven tool holder (The optional simple sub-spindle does not have this configuration)	—	●	—	●
主軸CS軸0.01° 定位	Main spindle CS axis 0.01° indexing	—	●	—	●
粗料套筒	Rough material bushing	●	●	●	●
同期迴轉套筒	Live Bushing	●	●	●	●
簡易背軸 (尾夾)	Simple sub-spindle (rear clamping device)	●	●	●	●
鐵屑機+鐵屑車 (只有配簡易背軸才有這個選項)	Chip conveyor + bucket (Only with simple sub-spindle has this option)	●	●	●	●



富格蘭科技有限公司
POLY GIM MACHINERY CO., LTD.

Web://www.polygim.com.tw

台灣苗栗縣銅鑼鄉竹森村149-1號 TEL: 886-37-981220 • 980599 FAX: 886-37-985306
No. 149-1, Zhusen Village, Tongluo Shiang, Miao-Li Country 366, Taiwan. • E-Mail: polygim@ms69.hinet.net



DIAMOND

SWISS TYPE CNC AUTO LATHE

● 走心式CNC自動車床

金鑽
12
SERIES



- Simplicity
- Precision
- Speed
- Durability
- Stability

LAIYIH SHYANG 230202, 1000 © Copy right reserved